

SIB-EB30V-C



Vortex86DX2 933MHz

1GB/2GB DDR2 RAM Onboard

Up to 4x RS-232

3x USB 2.0 Ports

1x 10/100 Ethernet

1x SD slot

AMI BIOS

1x SATA 2.0

2.5" SATA HDD/SSD Support

SATA DOM Support

15V 1.5A Wall Mount Power supply Included.

1x VGA

HD Audio Line Out

Mic Input (Optional)

TTL Level RS-232 (Optional)

Auto Power On

Ultra Low Power

Fanless Design

Wifi (Optional)

115 x 115 x 35mm

DC +8V ~ +15V

5 ~50° C

The EB-3330 & EB-3332 series is a revolutionary device which is especially designed for limited physical space and temperature concerns. No matter you are in a jammed office, a crowded place, or public transportation, the EB-3330 & EB-3332 can be easily integrated with a VESA LCD to bring it to access at any time. It can be attached to any VESA mounting fixture; allowing it to be securely mounted onto desks, walls, or buildings, and thereby optimizes your work area. It can also be attached directly to any size LCD for a mobile system for the use at trade shows, presentations, promotions, etc. Unlike traditional portable laptop design, the EB-3330 & 3332 series can be used with a large size LCD. Furthermore, with FANLESS design, the EB-3330 & EB-3332 series is ideal to be used in the environment where temperature demand is critical. So, if you are looking for a device that is able to provide you with more mobility & space but at the same time uses less power consumption, then the EB-3330 & 3332 series will be surely meet your need. The VESA® FDMI™ Standard defines mounting interfaces, hole patterns and associated cable/power supply locations for LCD monitors, plasma displays and other flat panel devices. The EB-3330 & 3332 series is designed to fit this standard to make monitor attachment quickly and easily.

Specifications

Processor:

Vortex86DX2

Clock Speed:

933 MHz

Real Time Clock:

Memory

RAM type:

DDR2 (Up to 2GB DDR2)

BIOS/ Bootloader:

AMI BIOS

Primary Flash:

1x 2.5 inch SATA HDD/SSD or DOM

Secondary Flash:

1x SD slot

Primary I/O

Video Out:

VGA

Audio:

HD Audio Line Out

Ethernet:

1x 10/100 Ethernet

USB:

3x USB 2.0 Ports

Serial Ports:

Up to 4x RS-232

Watchdog:

Secondary I/O

LAN Port:

Keypad:

PS/2:

Expansion
Bus:

Internal USB for WIFI

Analog
A/D:

D/A:

Dimensions
Dimensions:

4.5 × 4.5 × 1.38 in

Weight:

510 g

Power Requirements
Voltage:

8 V

Power Misc.:

DC +8 ~ +15V

Environmental
Low Operating Temperature:

-5 C

High Operating Temperature:

50 C

Pricing
SIB-EB30V-201-R

EB-3330-C2, Vortex86DX2 933MHz, 1GB RAM, 2x RS-232, 3xUSB2, 1xLAN, VGA

\$194.00

Order:

0

Parent Product:

SIB-EB30V-401-R

EB-3330-C4, Vortex86DX2 933MHz, 1GB RAM, 4x RS-232, 3xUSB2, 1xLAN, VGA

\$209.00

Order:

0

Parent Product:

SIB-EB32V-201-R

EB-3332-C2, Vortex86DX2 933MHz, 2GB RAM, 2x RS-232, 3xUSB2, 1xLAN, VGA

\$245.68

Order:

0

Parent Product:

SIB-EB32V-401-R

EB-3332-C4, Vortex86DX2 933MHz, 2GB RAM, 4x RS-232, 3xUSB2, 1xLAN, VGA

\$260.49

Order:

0

Parent Product:

Power Supply:

DC +8V ~ +15V (Included Wall Mount 15V 1.5A power supply)

Disk Interface:

1x SATA 2.0

Wireless:

Wifi (Optional)

Source URL: <https://www.emacinc.com/content/sib-eb30v-c>