

### MSDOS 6.22 Computer SIB-EB33J



Vortex86DX 600MHz

256/512MB DDR2 Onboard

3x USB 2.0 Ports

2x RS-232 Ports

1x 10/100 Ethernet

Compact Flash Slot

1x Micro SD Slot

1x Type I/II CF Slot

1x PS/2 for Keyboard/Mouse

1x IDE

Mini PCI Socket (Optional)

Wireless LAN (Optional)

AMI BIOS

VGA

Audio Mic In and Line Out

Auto Power On

Fanless Design

Real Time Clock

Ultra Low Power

+5v @ 2A (10W)

115 x 115 x 35mm

5 ~50°C

Full MS DOS 6.22 support MSDOS ROM DOS 6.22

The SIB-EB33J is a revolutionary device which is especially designed for limited physical space and temperature concerns. No matter you are in a jammed office, a crowded place, or public transportation, it can be easily integrated with a VESA LCD to bring you SIB-EB33J access at any time. It can attach to any VESA mounting fixture, allowing it to be securely mounted onto desks, walls, or buildings, and thereby optimizes your work area. It can also attach directly to any size LCD for a mobile system for the use at trade shows, presentations, promotions, etc. Unlike traditional portable laptop design, the SIB-EB33J can be used with a large size LCD. Furthermore, with FANLESS design, SIB-EB33J is ideal to be used in the environment where temperature demand is critical. So, if you are looking for a device that is able to provide you with more mobility & space but at the same time uses less power consumption, then eSIB-EB3RJ will be surely meet your need. The VESA® FDMI™ Standard defines mounting interfaces, hole patterns and associated cable/power supply locations for LCD monitors, plasma displays and other flat panel devices. SIB-EB3RJ is designed to fit this standard to make monitor attachment quick and

Processor Specifications

Vortex86DX

Clock Speed:

600 MHz

Real Time Clock:

Memory

RAM Type:

DDR2

BIOS/ Bootloader:

AMI BIOS

Primary Flash:

1x Compact Flash Type I/II Slot

Secondary Flash:

Micro SD Slot

Primary I/O

Video Out:

VGA

Audio:

1x Mic-In and Line-Out

Ethernet:

1x 10/100 Ethernet

USB:

3x USB 2.0 Ports

Serial Ports:

2x RS-232

Watchdog:

Secondary I/O

LAN Port:

Keypad:

PS/2:

Expansion  
Bus:

1x Mini PCI expansion slot

Analog  
A/D:

D/A:

Dimensions  
DIMENSIONS:

4.5 × 4.5 × 1.38 in

Weight:

520 g

Power Requirements  
Voltage:

5 V

Typical Current:

2 A

Environmental  
Low Operating Temperature:

5 C

High Operating Temperature:

50 C

Pricing  
SIB-EB33J-220-R

EBOX-3300A-JSK, Vortex86DX 800MHz, 256MB RAM, Compact Flash, microSD, 2xRS232, 3xUSB2, 1xLAN, Mini-PCI, Power supply,  
AUDIO, VGA

\$170.00

Order:

0

Parent Product:

SIB-EB33J-250-R

EBOX-3310A-JSK, Vortex86DX 800MHz, 512MB RAM, Compact Flash, microSD, 2xRS232, 3xUSB2, 1xLAN, Mini-PCI, Power supply,  
AUDIO, VGA

\$199.00

Order:

0

Parent Product:

Power Supply:

5V @ 2A (10W)

Disk Interface:

1x IDE

Compact flash

Wireless:

Optional

